

View Online at <https://aerobasegroup.com/nsn/6620-01-060-6418>

Scale Marking And Surface Finish:

Lined increments nonluminous and numerals nonluminous

Diameter:

1.940 inches

Length:

7.310 inches

Mounting Hole Diameter:

2.000 inches

Scale Division Quantity:

10 all indicators all scales

Current Type:

Ac

Ac Voltage Rating:

115.0 volts and 5.0 volts

Frequency Rating:

400.0 hertz

Contact Quantity:

12

End Application:

F-16 series aircraft

Contact Type:

Pin

Usage Design:

Rate of flow

Presentation Type:

Counter and dial

Scale Range:

+0.0/+80000.0 pounds per hour all indicators all scales

Individual Marking:

Fuel flow pphx1000

Electrical Connection Quantity:

1

Electrical Connection Identifying Number:

Ms27034h12b12p or equivalent

Pointer Type:

Indicating single pointer

Mounting Facility Type And Quantity:

1 bezel

Display Digit Quantity:

5

Accuracy Rating:

0.2 percent of flow rate all indicators all scales

Phase:

Single

Special Features:

Case in accordance with ms33639; scale color white on black background; hermatically sealed with 90 percent nitrogen and 10 percent helium at atmospheric pressure; used with tru-63/a, tru-63a-3 and tru-27/a transmitters, no auxilary voltage output signal

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A534d0