

View Online at <https://aerobasegroup.com/nsn/6620-01-270-7772>

**Scale Marking And Surface Finish:**

Numerals nonluminous

**Diameter:**

2.000 inches

**Length:**

6.000 inches

**Scale Division Quantity:**

5 single indicator single scale

**Current Type:**

Ac/dc

**Ac Voltage Rating:**

5.0 volts

**Dc Voltage Rating:**

28.0 volts

**Frequency Rating:**

400.0 hertz

**Contact Quantity:**

10

**End Application:**

F-16

**Contact Type:**

Pin

**Presentation Type:**

Dial

**Scale Range:**

+0.1/+100.0 percent revolutions per minute single indicator single scale

**Electrical Connection Quantity:**

1

**Electrical Connection Identifying Number:**

M83723-80h12126 or equivalent, mates w/m83723-75r12126 or equivalent

**Pointer Finish:**

Nonluminous single pointer

**Pointer Purpose:**

Percent of rated revolutions per minute

**Pointer Type:**

Indicating single pointer

**Mounting Facility Type And Quantity:**

1 bezel

**Accuracy Rating:**

1.0 percent revolutions per minute single indicator single scale

**Phase:**

Single

**Special Features:**

Tachometer, percent of rated speed, engine; case non-ferrous material; 5 vdc lighting circuit; 0-5 vdc buffered output signal proportional to engine speed; 10 second warm up time; receives operational signal from f100-pw-200/220 engine driven generator

**Color:**

White background

**Supplementary Features:**

Case per ms33639

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A532q0