

View Online at <https://aerobasegroup.com/nsn/6620-01-270-7772>

Scale Marking And Surface Finish:

Numerals nonluminous

Diameter:

2.000 inches

Length:

6.000 inches

Scale Division Quantity:

5 single indicator single scale

Current Type:

Ac/dc

Ac Voltage Rating:

5.0 volts

Dc Voltage Rating:

28.0 volts

Frequency Rating:

400.0 hertz

Contact Quantity:

10

End Application:

F-16

Contact Type:

Pin

Presentation Type:

Dial

Scale Range:

+0.1/+100.0 percent revolutions per minute single indicator single scale

Electrical Connection Quantity:

1

Electrical Connection Identifying Number:

M83723-80h12126 or equivalent, mates w/m83723-75r12126 or equivalent

Pointer Finish:

Nonluminous single pointer

Pointer Purpose:

Percent of rated revolutions per minute

Pointer Type:

Indicating single pointer

Mounting Facility Type And Quantity:

1 bezel

Accuracy Rating:

1.0 percent revolutions per minute single indicator single scale

Phase:

Single

Special Features:

Tachometer, percent of rated speed, engine; case non-ferrous material; 5 vdc lighting circuit; 0-5 vdc buffered output signal proportional to engine speed; 10 second warm up time; receives operational signal from f100-pw-200/220 engine driven generator

Color:

White background

Supplementary Features:

Case per ms33639

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A532q0