

View Online at <https://aerobasegroup.com/nsn/6625-00-003-0975>

Circuit Current For Which Designed:

Ac

Overall Length:

2.060 inches

Mounting Hole Diameter:

Between 0.143 inches and 0.157 inches

Scale Division Quantity:

14 single indicator single range

Overall Diameter:

3.510 inches

End Application:

Generator set, 30kw, 60 hz, skid mounted (3id) (mep-007a), generator set, diesel engine, 200kw, mep009a, generator set, tact quiet, 60kw, 400hz, mep-816a, missile, air launch cruise (alcm) agm-86b, radar set, lightweight 3d (an/tps-59), shipboard material handling equipment (mhe), generator set, diesel engine, 100kw, pu-495, safeguard class ars, generator, 15kw, diesel, military standard family, generator set, 60kw, 60 hz, skid-mounted (2id) (mep-006a)

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.000 to 2.000 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.660 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 133.0 ohms single indicator single range

Criticality Code Justification:

Feat

Circuit Attachment Method And Quantity:

2 screw

Special Features:

Blue line at 83 percent, red line at 100 percent; weapon system essential

Style Designator:

Round flush mta

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0