

View Online at <https://aerobasegroup.com/nsn/6625-00-003-2993>

Circuit Current For Which Designed:

Dc

Overall Length:

2.550 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches

Overall Height:

3.120 inches

Overall Width:

3.270 inches

Scale Division Quantity:

60 single indicator single range

Mounting Stud Length:

0.620 inches

Environmental Protection:

Humidity proof

Furnished Items And Quantity:

Term. Hdw 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

120.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Panel For Which Designed:

Unable to decode or nonmagnetic

Meter Depth Behind Mounting Flange:

1.160 inches

Meter Body Diameter Behind Mounting Flange:

2.790 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+60.0 milliamperes, dc single indicator single range

Circuit Construction Type:

Nonelectronic

Mounting Stud Diameter:

0.112 inches

Scale Selection Method:

Terminal

Features Provided:

External shunting and magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Conforms to ansi c39.1-1964

Style Designator:

Rectangular flush mtg

Supplementary Features:

1000 ohms min internal resistance

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0