NSN 6625-00-003-7040



Oscilloscope - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6625-00-003-7040 **Overall Length:** 18.688 inches **Overall Height:** 11.750 inches **Overall Width:** 8.312 inches **Current Type:** Ac Frequency Rating: Between 50.0 hertz and 400.0 hertz Voltage Rating: Between 115.0 volts and 230.0 volts **Beam Quantity: Mounting Method:** Rack Screen Size: 5 in. **Sweep Circuits:** Not included **Amplifier Deflection Sensitivity Provision:** Provided **Vertical Deflection Sensitivity Voltage Rating:** 0.1 millivolts rms per inch and 20.0 millivolts rms per inch **Horizontal Deflection Sensitivity Voltage Rating:** 0.1 volts cw outside diameter and 2.5 volts rms per inch **Input Intensity Modulation Feature:** Provided **Visual Modulation Sensitivity Voltage Rating:** 5.0 kilovolts **Plate Direct Connection Deflection Sensitivity Provision:** Not provided Frequency Response Rating: Not provided **Amplifier Input Impedance Rating Provision:** Provided **Amplitude Calibrating Voltage Waveform:** Square wave **Calibrated Screen Scale:**

Included

Included

Trace Storage Tube:

NSN 6625-00-003-7040

Oscilloscope - Page 2 of 2



Camera Recording Device Accommodation:
Not provided
Phase:
Single
Functional Classification:
Aa-3.2
Functional Description:
Solid state dual channel oscilloscope used in the 500 khz frequency range
Entry Date:
89-04-06
Reference Data And Literature:
33a1-3-221-2
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
T320-g