

View Online at <https://aerobasegroup.com/nsn/6625-00-003-7251>

Circuit Current For Which Designed:

Dc

Overall Length:

2.218 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.281 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.593 inches

Overall Height:

4.093 inches

Overall Width:

4.656 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

24 single indicator 2nd range

Environmental Protection:

Shock resistant and vibration resistant

Barrel Width:

2.000 inches

Furnished Items And Quantity:

Shunt wire 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black and blue and green single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

2.156 inches

Meter Body Width Behind Mounting Flange:

4.500 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Red single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

-11.0 to 1.0 decibels above or below one milliwatt single indicator 1st range

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

4.031 inches

Meter Barrel Depth:

1.500 inches

Features Provided:

Mirror scale

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Bat, good

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Style Designator:

Rectangular flush mtg barrel, down

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0