NSN 6625-00-003-8788

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-003-8788

| Circuit Current For Which Designed: |
|---|
| Dc |
| Dielectric Withstanding Voltage In Volts: |
| 2600.0 |
| Overall Length: |
| 2.350 inches |
| Overall Height: |
| 2.690 inches |
| Overall Width: |
| 2.690 inches |
| Scale Division Quantity: |
| 60 single indicator single range |
| Mounting Stud Length: |
| 0.500 inches |
| Mounting Bolt Circle Diameter: |
| 2.440 inches |
| Furnished Items And Quantity: |
| Nuts 3, washers 2 |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Sensitivity Rating: |
| 1000.0 ohms per volt |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0 to 2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.180 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.150 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Power Source: |
| |

NSN 6625-00-003-8788

Voltmeter - Page 2 of 2



Mounting Facility Type And Quantity: 3 threaded stud **Scale Graduation Type:** Linear single indicator single range Measurement Range: +0.0 to 30.0 volts, dc single indicator single range **Mounting Stud Diameter:** 0.112 inches **Features Provided:** Magnetic shield and zero adjuster **Movement Suspension Method:** Jewel pivot base **Circuit Attachment Method And Quantity:** 2 binding post **Nuclear Hardness Critical Feature:** Nonhardened **Style Designator:** Rectangular flush mtg Shelf Life: N/a **Unit Of Measure:** Demilitarization:

.,

Yes - demil/mli

Fiig:

A310a0