

View Online at <https://aerobasegroup.com/nsn/6625-00-004-9536>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

1000.0

**Overall Depth:**

3.125 inches

**Overall Length:**

7.000 inches

**Overall Width:**

5.250 inches

**Scale Division Quantity:**

50 single indicator 2nd range

**Furnished Items And Quantity:**

Leads, test 2; batteries 2; manual 1

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Hand held

**Frequency Response Range:**

+0.020 to 50.000 kilohertz

**Sensitivity Rating:**

1000.0 ohms per volt

**Dial Scale Marking Color:**

Red single indicator 2nd range

**Accuracy In Percent:**

-3.0 to 3.0 at full scale single indicator 2nd range

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Red single indicator all ranges

**Power Source:**

Internal

**Scale Graduation Type:**

Nonlinear single indicator 4th range

**Measurement Range:**

+0.0 to 1000.0 volts, dc single indicator 1st range

**Scale Selection Method:**

Switch

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 wire lead

**Special Features:**

Ohms accuracy is form 1 deg. Of arc; measures from neg. 20 to pos. 50 decibles

**Material:**

Plastic phenolic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Portable

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0