## NSN 6625-00-005-5527

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-005-5527

Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
2.650 inches
Mounting Hole Diameter:
Between 0.120 inches and 0.130 inches
Scale Division Quantity:
10 single indicator 1st range
Overall Diameter:
2.695 inches
Environmental Protection:
Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight
Mounting Bolt Circle Diameter:
2.440 inches
Furnished Items And Quantity:
Nut 3; washer 3
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
100.0 microamperes
Dial Scale Marking Color:
Black single indicator 2nd range and green single indicator 2nd range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator all ranges
Panel For Which Designed:
Magnetic or nonmagnetic
Meter Depth Behind Mounting Flange:
1.475 inches
Meter Body Diameter Behind Mounting Flange:
2.210 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator all ranges
Pointer Color:

Black single indicator all ranges

## NSN 6625-00-005-5527

Special Scale Meter - Page 2 of 2



Scale Marking:
Top scale: -50, -40, -30, -20, -10, 13325, 10, 20, 30, 40, 50; bot scale: I, mhz, r
Mounting Facility Type And Quantity:
3 screw and 3 unthreaded hole
Scale Graduation Type:
Nonlinear single indicator 2nd range
Features Provided:
Luminous scale marking and magnetic shield and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Special Features:
Ruggedized; terminal position from 0.510 in. Above center line to 0.260 in below center line
Special Markings:
Green band 46 to 54 ua on bot scale
Material:
Stainless steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel semigloss
Special Test Features:
Conforms to mil-m-10304/5, type mr26w100dcuar
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

Fiig:

A310a0