

View Online at <https://aerobasegroup.com/nsn/6625-00-005-5531>

Circuit Current For Which Designed:

Dc

Overall Length:

1.592 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.708 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.708 inches

Overall Height:

Between 0.865 inches and 0.890 inches

Overall Width:

Between 0.865 inches and 0.890 inches

Mounting Hole Diameter:

0.098 inches

Scale Division Quantity:

2 single indicator single range

Environmental Protection:

Shock resistant and vibration resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

50.0 microamperes

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-5.0 to 5.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.095 inches

Meter Body Diameter Behind Mounting Flange:

0.850 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator single range

Pointer Color:

Black and red single indicator single range

Scale Marking:

White band m 25 ua to p 25 ua deflection

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0