

View Online at <https://aerobasegroup.com/nsn/6625-00-006-4261>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

2.650 inches

Mounting Stud Length:

0.500 inches

Overall Diameter:

2.695 inches

Mounting Bolt Circle Diameter:

2.440 inches

Furnished Items And Quantity:

Mtg hdw 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

700.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.5 to 2.5 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.600 inches

Meter Body Diameter Behind Mounting Flange:

2.210 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Unmarked other than colored scale

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Mounting Stud Diameter:

0.112 inches

Features Provided:

Knife edge pointer and self-illumination facility and zero adjuster

Criticality Code Justification:

Mark

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 solder lug and 2 solder stud

Special Features:

Ruggedized; external calibration adjust

Special Markings:

Green 485 ua to 495 ua and 505 ua to 515 ua, orange 475 ua to 485 ua and 515 ua to 525 ua, blue 450 ua to 475 ua and 525 ua to 550 ua, white 400 ua to 450 ua and 550 ua to 600 ua

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel semigloss

Special Test Features:

0.950 ohm resistance

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0