

View Online at <https://aerobasegroup.com/nsn/6625-00-006-7638>

Circuit Current For Which Designed:

Dc

Overall Length:

11.375 inches

Overall Height:

5.125 inches

Overall Width:

6.500 inches

Scale Division Quantity:

60 single indicator 3rd range

Frequency Rating:

Between 48.0 hertz and 440.0 hertz

End Application:

B-52 aircraft

Furnished Items And Quantity:

Power cable 1; thermistor mount cable 1

Indicator Type:

Dial w/pointer

Installation Design:

Bench

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-1.0 to 1.0 at full scale single indicator all ranges

Background Color:

White single indicator all ranges

Pointer Color:

Red single indicator all ranges

Power Source:

External

Scale Graduation Type:

Nonlinear single indicator 1st range

Measurement Range:

-10.0 to 0.0 decibels above or below one milliwatt single indicator 1st range

Scale Selection Method:

Switch

Features Provided:

Electrical overload protection and internal battery accommodation and mirror scale and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

1 plug

Operating Voltage Rating In Volts:

Between 115.0 ac and 230.0 ac

Special Features:

V rf input; v comp input; recorder output; line v slide switch

Special Markings:

Rechg bat left side of scale; mw range: 0.01, 0.03, 0.1, 0.3, 1.0, 3.0, 10.0; db range: -20.0, -15.0, -10.0, -5.0, 0, 5.0, 10.0; cal factor: 88, 90, 92, 94, 96, 98, 100; mt res; 100, 200

Style Designator:

Rectangular or square

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0