

View Online at <https://aerobasegroup.com/nsn/6625-00-006-7638>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

11.375 inches

**Overall Height:**

5.125 inches

**Overall Width:**

6.500 inches

**Scale Division Quantity:**

60 single indicator 3rd range

**Frequency Rating:**

Between 48.0 hertz and 440.0 hertz

**End Application:**

B-52 aircraft

**Furnished Items And Quantity:**

Power cable 1; thermistor mount cable 1

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Bench

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-1.0 to 1.0 at full scale single indicator all ranges

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Red single indicator all ranges

**Power Source:**

External

**Scale Graduation Type:**

Nonlinear single indicator 1st range

**Measurement Range:**

-10.0 to 0.0 decibels above or below one milliwatt single indicator 1st range

**Scale Selection Method:**

Switch

**Features Provided:**

Electrical overload protection and internal battery accommodation and mirror scale and zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

1 plug

**Operating Voltage Rating In Volts:**

Between 115.0 ac and 230.0 ac

**Special Features:**

V rf input; v comp input; recorder output; line v slide switch

**Special Markings:**

Rechg bat left side of scale; mw range: 0.01, 0.03, 0.1, 0.3, 1.0, 3.0, 10.0; db range: -20.0, -15.0, -10.0, -5.0, 0, 5.0, 10.0; cal factor: 88, 90, 92, 94, 96, 98, 100; mt res; 100, 200

**Style Designator:**

Rectangular or square

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0