NSN 6625-00-007-2866

Ammeter - Page 1 of 2

3 unthreaded hole



View Online at https://aerobasegroup.com/nsn/6625-00-007-2866

Circuit Current For Which Designed:
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
2.650 inches
Mounting Hole Diameter:
Between 0.120 inches and 0.130 inches
Scale Division Quantity:
40 single indicator single range
Overall Diameter:
2.695 inches
Environmental Protection:
Shock resistant and vibration resistant
Mounting Bolt Circle Diameter:
2.440 inches
Furnished Items And Quantity:
Nut 5; washer 5
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
1.600 inches
Meter Body Diameter Behind Mounting Flange:
2.210 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Power Source:
External
Mounting Facility Type And Quantity:
3 unthreaded hole

NSN 6625-00-007-2866

Ammeter - Page 2 of 2



Line	ar single indicator single range
	surement Range:
	/+200.0 microamperes, dc single indicator single range
Feat	tures Provided:
Exte	rnal shunting and luminous scale marking and magnetic shield and zero adjus
Mov	ement Suspension Method:
Jew	el pivot base
Circ	uit Attachment Method And Quantity:
2 th	readed stud
Spe	cial Features:
Rug	gedized
Spe	cial Markings:
Sea	ed do not open on back of meter
Mate	erial:
Stai	nless steel
Surf	ace Treatment:
Ena	mel semigloss
Spe	cial Test Features:
Con	forms to mil-m-10304/5
Styl	e Designator:
Rou	nd flush mtg
Fsc	Application Data:
Test	set, elect. Equip.
She	If Life:
N/a	
Unit	Of Measure:
Dem	nilitarization:
No	
Fiig	
A31	Da0