NSN 6625-00-007-5956

Ammeter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-00-007-5956

Circuit Current For Which Designed:
Dc
Overall Length:
2.820 inches
Mounting Hole Diameter:
0.150 inches
Overall Diameter:
3.510 inches
Mounting Bolt Circle Diameter:
3.160 inches
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
200.0 microamperes
Meter Depth Behind Mounting Flange:
1.660 inches
Meter Body Diameter Behind Mounting Flange:
2.800 inches
Movement Type:
Movement Type: Moving iron vane
Moving iron vane
Moving iron vane Mounting Facility Type And Quantity:
Moving iron vane Mounting Facility Type And Quantity: 3 unthreaded hole
Moving iron vane Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range:
Moving iron vane Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: -2.5/+2.5 milliamperes, dc 2nd indicator 2nd range
Moving iron vane Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: -2.5/+2.5 milliamperes, dc 2nd indicator 2nd range Circuit Attachment Method And Quantity:
Moving iron vane Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: -2.5/+2.5 milliamperes, dc 2nd indicator 2nd range Circuit Attachment Method And Quantity: 2 threaded stud
Moving iron vane Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: -2.5/+2.5 milliamperes, dc 2nd indicator 2nd range Circuit Attachment Method And Quantity: 2 threaded stud Special Markings:
Moving iron vane Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: -2.5/+2.5 milliamperes, dc 2nd indicator 2nd range Circuit Attachment Method And Quantity: 2 threaded stud Special Markings: Green area from m73 to m83ua marked batt chk
Moving iron vane Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: -2.5/+2.5 milliamperes, dc 2nd indicator 2nd range Circuit Attachment Method And Quantity: 2 threaded stud Special Markings: Green area from m73 to m83ua marked batt chk Style Designator:
Moving iron vane Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: -2.5/+2.5 milliamperes, dc 2nd indicator 2nd range Circuit Attachment Method And Quantity: 2 threaded stud Special Markings: Green area from m73 to m83ua marked batt chk Style Designator: Round flush mtg
Moving iron vane Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: -2.5/+2.5 milliamperes, dc 2nd indicator 2nd range Circuit Attachment Method And Quantity: 2 threaded stud Special Markings: Green area from m73 to m83ua marked batt chk Style Designator: Round flush mtg Shelf Life:
Moving iron vane Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: -2.5/+2.5 milliamperes, dc 2nd indicator 2nd range Circuit Attachment Method And Quantity: 2 threaded stud Special Markings: Green area from m73 to m83ua marked batt chk Style Designator: Round flush mtg Shelf Life: N/a
Moving iron vane Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: -2.5/+2.5 milliamperes, dc 2nd indicator 2nd range Circuit Attachment Method And Quantity: 2 threaded stud Special Markings: Green area from m73 to m83ua marked batt chk Style Designator: Round flush mtg Shelf Life: N/a
Moving iron vane Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: -2.5/+2.5 milliamperes, dc 2nd indicator 2nd range Circuit Attachment Method And Quantity: 2 threaded stud Special Markings: Green area from m73 to m83ua marked batt chk Style Designator: Round flush mtg Shelf Life: N/a Unit Of Measure:
Moving iron vane Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: -2.5/+2.5 milliamperes, dc 2nd indicator 2nd range Circuit Attachment Method And Quantity: 2 threaded stud Special Markings: Green area from m73 to m83ua marked batt chk Style Designator: Round flush mtg Shelf Life: N/a Unit Of Measure: Demilitarization: