NSN 6625-00-008-2327

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-008-2327

Circuit Current For Which Designed:
Dc
Overall Length:
1.540 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.880 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.880 inches
Overall Height:
2.470 inches
Overall Width:
2.470 inches
Scale Division Quantity:
50 single indicator single range
Mounting Stud Length:
0.540 inches
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Mounting Arrangement Style: Four hole/stud rectangular/square
Four hole/stud rectangular/square
Four hole/stud rectangular/square Sensitivity Rating:
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color:
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent:
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all ranges
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all ranges Unable To Decode:
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all ranges Unable To Decode: Unable to decode or unable to decode
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all ranges Unable To Decode: Unable to decode or unable to decode Meter Depth Behind Mounting Flange:
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all ranges Unable To Decode: Unable to decode or unable to decode Meter Depth Behind Mounting Flange: 1.060 inches
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all ranges Unable To Decode: Unable to decode or unable to decode Meter Depth Behind Mounting Flange: 1.060 inches Meter Body Diameter Behind Mounting Flange:
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all ranges Unable To Decode: Unable to decode or unable to decode Meter Depth Behind Mounting Flange: 1.060 inches Meter Body Diameter Behind Mounting Flange: 2.170 inches
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all ranges Unable To Decode: Unable to decode or unable to decode Meter Depth Behind Mounting Flange: 1.060 inches Meter Body Diameter Behind Mounting Flange: 2.170 inches Movement Type:
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all ranges Unable To Decode: Unable to decode or unable to decode Meter Depth Behind Mounting Flange: 1.060 inches Meter Body Diameter Behind Mounting Flange: 2.170 inches Movement Type: Moving coil, permanent magnet
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all ranges Unable To Decode: Unable to decode or unable to decode Meter Depth Behind Mounting Flange: 1.060 inches Meter Body Diameter Behind Mounting Flange: 2.170 inches Movement Type: Moving coil, permanent magnet Background Color:

4 flange

Mounting Facility Type And Quantity:

NSN 6625-00-008-2327

Voltmeter - Page 2 of 2



Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0 to 5.0 volts, $$ dc single indicator single range
Mounting Stud Diameter:
0.125 inches
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Material:
Plastic phenolic
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Rectangular flush mtg
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A310a0