

View Online at <https://aerobasegroup.com/nsn/6625-00-008-6787>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

1.990 inches

Overall Height:

2.500 inches

Overall Width:

2.690 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

17 single indicator single range

Environmental Protection:

Dustproof

Distance Between Mounting Facility Centers:

2.110 inches

Furnished Items And Quantity:

Nut 8; lockwasher 5; seal 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

0.930 inches

Meter Body Diameter Behind Mounting Flange:

1.450 inches

Movement Type:

Electrostatic

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-24.0 to 6.0 decibels single indicator single range

Features Provided:

Magnetic shield and zero adjuster

Circuit Attachment Method And Quantity:

3 threaded stud

Special Features:

Ruggedized

Special Markings:

Green band from minus 6 to plus 5, red band from plus 5 to plus 6

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel lusterless

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set electronic

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0