

View Online at <https://aerobasegroup.com/nsn/6625-00-009-2397>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

2.030 inches

**Mounting Hole Diameter:**

Between 0.120 inches and 0.130 inches

**Scale Division Quantity:**

50 single indicator single range

**Overall Diameter:**

2.695 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Mounting Bolt Circle Diameter:**

2.440 inches

**Furnished Items And Quantity:**

Nut 5; washer 5

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator single range

**Panel For Which Designed:**

Nonmagnetic

**Meter Depth Behind Mounting Flange:**

1.170 inches

**Meter Body Diameter Behind Mounting Flange:**

2.150 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 screw and 3 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0 to 25.0 milliamperes, ac single indicator single range

**Circuit Construction Type:**

Nonelectronic

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Ruggedized

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Special Test Features:**

Complies with mil-m-10304

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0