

View Online at <https://aerobasegroup.com/nsn/6625-00-009-5512>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

1000.0

**Overall Length:**

2.296 inches

**Mounting Hole Diameter:**

0.116 inches

**Overall Diameter:**

2.687 inches

**Environmental Protection:**

Waterproof

**Mounting Bolt Circle Diameter:**

2.440 inches

**Furnished Items And Quantity:**

Mtg hdw 3; term. Hdw 2

**Indicator Type:**

Vibrating reed

**Installation Design:**

Panel

**Register Quantity:**

1

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Dial Scale Marking Color:**

Black single indicator single range

**Resonant Reed Quantity:**

5

**Accuracy In Percent:**

-0.3 to 0.3 at full scale single indicator single range

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

1.375 inches

**Meter Body Diameter Behind Mounting Flange:**

2.156 inches

**Movement Type:**

Vibrating reed

**Background Color:**

White single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Measurement Range:**

+58.0 to 62.0 hertz single indicator single range

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Reeds have high q characteristics

**Material:**

Plastic phenol-formaldehyde

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel

**Style Designator:**

Round flush mtg

**Supplementary Features:**

Temp compensations not required

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0