

View Online at <https://aerobasegroup.com/nsn/6625-00-010-5128>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

2.075 inches

**Mounting Hole Diameter:**

0.150 inches

**Scale Division Quantity:**

30 single indicator single range

**Overall Diameter:**

3.500 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Mounting Bolt Circle Diameter:**

3.160 inches

**Furnished Items And Quantity:**

Term. Hdw 4

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Sensitivity Rating:**

5.0 microamperes

**Dial Scale Marking Color:**

Black and green single indicator single range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator single range

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

1.200 inches

**Meter Body Diameter Behind Mounting Flange:**

2.650 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Scale Marking:**

Zero centerline w/scale to 30 on both ends

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Features Provided:**

Self-illumination facility

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

4 solder lug

**Special Features:**

Ruggedized

**Special Markings:**

Green band from p 12 to p 18; cw; adjust z bias pot; ccw

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel

**Special Test Features:**

Conforms to mil-m-10304

**Style Designator:**

Round flush mtg

**Supplementary Features:**

Type 327 lamp; two of term. For lamp

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0