

View Online at <https://aerobasegroup.com/nsn/6625-00-014-6029>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

2.094 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

5.250 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.000 inches

**Overall Height:**

4.437 inches

**Overall Width:**

5.812 inches

**Scale Division Quantity:**

50 single indicator 1st range

**Mounting Stud Length:**

0.281 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Dial Scale Marking Color:**

Red single indicator 1st range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

1.250 inches

**Meter Body Diameter Behind Mounting Flange:**

2.641 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Nonlinear single indicator 3rd range

**Measurement Range:**

+3.0 to 10.0 volts, root mean square single indicator 3rd range

**Mounting Stud Diameter:**

0.125 inches

**Scale Selection Method:**

Terminal

**Features Provided:**

External shunting and mirror scale and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Ruggedized

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A310a0