

View Online at <https://aerobasegroup.com/nsn/6625-00-017-8143>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

500.0

**Overall Length:**

2.944 inches

**Overall Height:**

2.145 inches

**Overall Width:**

0.910 inches

**Mounting Hole Diameter:**

0.120 inches

**Scale Division Quantity:**

21 single indicator single range

**Distance Between Mounting Facility Centers:**

1.906 inches

**Furnished Items And Quantity:**

Screws 2; lock washers 2; hex nuts 2

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Two hole/stud

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Panel For Which Designed:**

Nonmagnetic

**Meter Depth Behind Mounting Flange:**

1.993 inches

**Meter Body Width Behind Mounting Flange:**

0.630 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0 to 200.0 amperes, dc single indicator single range

**Circuit Construction Type:**

Electronic, solid state

**Scale Selection Method:**

Terminal

**Meter Body Height Behind Mounting Flange:**

1.710 inches

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder stud

**Material:**

Copper alloy

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular semi-flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A310a0