NSN 6625-00-018-9061

Ammeter - Page 1 of 2

Ac

Overall Length:
4.281 inches
Overall Height:
4.531 inches
Overall Width:
4.531 inches

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-018-9061

| Furnished Items And Quantity: |
|---------------------------------------------------------|
| Nut 6; washer 6 |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Sensitivity Rating: |
| 5.0 amperes |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Panel For Which Designed: |
| Nonmagnetic |
| Meter Body Diameter Behind Mounting Flange: |
| 3.938 inches |
| Movement Type: |
| Moving iron vane |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Power Source: |
| External |
| Mounting Facility Type And Quantity: |
| 4 screw and 4 unthreaded hole |
| Scale Graduation Type: |
| Nonlinear single indicator single range |
| Measurement Range: |
| +0.0 to 600.0 amperes, ac single indicator single range |
| Features Provided: |
| Zero adjuster |
| |

NSN 6625-00-018-9061

Ammeter - Page 2 of 2



| Movement Suspension Method: |
|-----------------------------------------|
| Taut band |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Material: |
| Plastic and steel |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Rectangular flush mtg |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiia: |

A310a0