## NSN 6625-00-020-8932

Special Scale Meter - Page 1 of 2

**Circuit Current For Which Designed:** 

**Overall Length:** 



View Online at https://aerobasegroup.com/nsn/6625-00-020-8932

2.330 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.870 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.870 inches
Overall Height:
2.370 inches
Overall Width:
2.370 inches
Mounting Stud Length:
0.520 inches
Furnished Items And Quantity:
Lock washers 4; hex nuts 4
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0 to 2.0 at full scale single indicator single range
Panel For Which Designed:
Nonmagnetic
Meter Depth Behind Mounting Flange:
2.130 inches
Meter Body Diameter Behind Mounting Flange:
2.170 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Scale Marking:

4 threaded stud

Red area; yellow area; green area

Mounting Facility Type And Quantity:

## NSN 6625-00-020-8932

Special Scale Meter - Page 2 of 2



Scale Graduation Type:
Nonlinear single indicator single range
Mounting Stud Diameter:
0.112 inches
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
<b>Circuit Attachment Method And Quantity:</b>
2 threaded stud
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A310a0