

View Online at <https://aerobasegroup.com/nsn/6625-00-021-6967>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

1.310 inches

Scale Division Quantity:

20 single indicator single range

Overall Diameter:

1.688 inches

Environmental Protection:

Cold resistant and heat resistant and watertight

Furnished Items And Quantity:

O ring 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-3.0 to 3.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.765 inches

Meter Body Diameter Behind Mounting Flange:

1.500 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Pa set; dr set; nom; line

Mounting Facility Type And Quantity:

1 threaded body and 1 threaded ring

Scale Graduation Type:

Linear single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

250 mv maximum power consumption

Special Markings:

Black band from 0.575 to 0.775 ma deflection

Material:

Aluminum

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Anodize

Special Test Features:

Conforms w/mil-m-17275

Style Designator:

Round flush mtg

Supplementary Features:

100 ohms term. Res

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0