

View Online at <https://aerobasegroup.com/nsn/6625-00-023-7421>

Circuit Current For Which Designed:

Ac

Overall Length:

1.594 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches

Overall Height:

2.969 inches

Overall Width:

2.969 inches

Scale Division Quantity:

75 single indicator single range

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

1000.0 ohms per volt

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.344 inches

Meter Body Diameter Behind Mounting Flange:

2.719 inches

Background Color:

White single indicator single range

Mounting Facility Type And Quantity:

4 threaded stud

Measurement Range:

+0.0 to 150.0 volts, ac single indicator single range

Mounting Stud Diameter:

0.109 inches

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Rectifier type

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Reference Number Differentiating Characteristics:

As differentiated by measurement range per indicator

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0