

View Online at <https://aerobasegroup.com/nsn/6625-00-031-0249>

Circuit Current For Which Designed:

Dc

Overall Length:

1.860 inches

Overall Height:

2.900 inches

Overall Width:

4.500 inches

Scale Division Quantity:

60 single indicator single range

Mounting Stud Length:

0.500 inches

Distance Between Mounting Facility Centers:

3.500 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

1000.0 ohms per volt

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.310 inches

Meter Body Diameter Behind Mounting Flange:

2.180 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

2 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 300.0 kilovolts, dc single indicator single range

Mounting Stud Diameter:

0.164 inches

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 binding post

Special Features:

Ruggedized

Material:

Plastic phenolic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiiq:

A310a0