

View Online at <https://aerobasegroup.com/nsn/6625-00-033-0780>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

2.220 inches

**Overall Height:**

2.730 inches

**Overall Width:**

3.150 inches

**Scale Division Quantity:**

50 single indicator single range

**Mounting Stud Length:**

0.450 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Mounting Bolt Circle Diameter:**

2.440 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Sensitivity Rating:**

50.0 millivolts

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator single range

**Panel For Which Designed:**

Magnetic or nonmagnetic

**Meter Depth Behind Mounting Flange:**

1.010 inches

**Meter Body Diameter Behind Mounting Flange:**

2.190 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 threaded stud

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0 to 100.0 amperes, dc single indicator single range

**Mounting Stud Diameter:**

0.125 inches

**Features Provided:**

Magnetic shield and zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Meets ansi c39.1

**Material:**

Plastic polycarbonate

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Supplementary Features:**

Ruggedized thermoplastic

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0