NSN 6625-00-037-9481

Ammeter - Page 1 of 2

Circuit Current For Which Designed:

Dielectric Withstanding Voltage In Volts:



View Online at https://aerobasegroup.com/nsn/6625-00-037-9481

3
3000.0
Overall Length:
2.650 inches
Mounting Hole Diameter:
Between 0.120 inches and 0.130 inches
Scale Division Quantity:
50 single indicator all ranges
Overall Diameter:
2.695 inches
Environmental Protection:
Shock resistant and vibration resistant
Mounting Bolt Circle Diameter:
2.440 inches
Furnished Items And Quantity:
Nut 7; washer 7
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
5.0 milliamperes
Dial Scale Marking Color:
Black single indicator all ranges
Accuracy In Percent:
-2.0 to 2.0 at full scale single indicator all ranges
Panel For Which Designed:
Unable to decode or nonmagnetic
Meter Depth Behind Mounting Flange:
1.600 inches
Meter Body Diameter Behind Mounting Flange:
2.210 inches
Movement Type:
Moving iron vane
Background Color:
White single indicator all ranges
Pointer Color:
Black single indicator all ranges

NSN 6625-00-037-9481

Ammeter - Page 2 of 2



Power Source:
External
Mounting Facility Type And Quantity:
3 screw and 3 unthreaded hole
Scale Graduation Type:
Linear single indicator all ranges
Measurement Range:
+0.0/+5.0 milliamperes, ac single indicator 1st range
Features Provided:
Magnetic shield and zero adjuster
Movement Suspension Method:
Taut band
Circuit Attachment Method And Quantity:
2 solder lug
Special Features:
Ruggedized
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel
Special Test Features:
Conforms to mil-m-10304/9, type mr26w specr
Style Designator:
Round flush mtg
Fsc Application Data:
Elec. Elect. Properties measuring and test instruments
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0