

View Online at <https://aerobasegroup.com/nsn/6625-00-042-5434>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

2000.0

Overall Length:

4.750 inches

Overall Height:

1.430 inches

Overall Width:

4.160 inches

Mounting Hole Diameter:

0.165 inches

Scale Division Quantity:

25 single indicator 2nd range

Distance Between Mounting Facility Centers:

3.787 inches

Furnished Items And Quantity:

Screw 6; nut 4; washer 2; bezel 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Frequency Response Range:

+0.020 to 20.000 kilohertz

Sensitivity Rating:

100.0 microamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

4.230 inches

Meter Body Width Behind Mounting Flange:

3.430 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

2 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator 1st range

Measurement Range:

-15.0 to 2.0 decibels above or below one milliwatt single indicator 1st range

Meter Body Height Behind Mounting Flange:

1.390 inches

Features Provided:

Electrical overload protection and knife edge pointer and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Horiz mtg

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Anodize and enamel

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0