

View Online at <https://aerobasegroup.com/nsn/6625-00-045-3414>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.500 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

30 single indicator single range

Overall Diameter:

2.687 inches

Environmental Protection:

Cold resistant and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Mounting Bolt Circle Diameter:

2.220 inches

Furnished Items And Quantity:

Nut 5; lockwasher 5; spacer

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.281 inches

Meter Body Diameter Behind Mounting Flange:

2.187 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 600.0 volts, dc single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Sealed

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0