NSN 6625-00-047-4002

Multiple Scale Meter - Page 1 of 2

Circuit Current For Which Designed:

Dc

Overall Length: 2.250 inches

0.150 inches

Mounting Hole Diameter:

Scale Division Quantity:



View Online at https://aerobasegroup.com/nsn/6625-00-047-4002

| 50 single indicator all ranges |
|---|
| Overall Diameter: |
| 3.500 inches |
| Mounting Bolt Circle Diameter: |
| 3.160 inches |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Sensitivity Rating: |
| 50.0 milliamperes |
| Dial Scale Marking Color: |
| White single indicator all ranges |
| Accuracy In Percent: |
| -2.0 to 2.0 at full scale single indicator all ranges |
| Meter Depth Behind Mounting Flange: |
| 1.750 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.800 inches |
| Background Color: |
| Black single indicator all ranges |
| Pointer Color: |
| White single indicator all ranges |
| Power Source: |
| External |
| Mounting Facility Type And Quantity: |
| 3 unthreaded hole |
| Scale Graduation Type: |
| Linear single indicator all ranges |
| Measurement Range: |
| -25.0 to 25.0 milliamperes, dc single indicator 1st range |
| Circuit Attachment Method And Quantity: |
| 2 solder lug |

NSN 6625-00-047-4002

Multiple Scale Meter - Page 2 of 2



| Material: |
|---|
| Steel |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Round flush mtg |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A310a0