

View Online at <https://aerobasegroup.com/nsn/6625-00-049-8366>

Circuit Current For Which Designed:

Dc

Overall Length:

1.812 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches

Overall Height:

3.130 inches

Overall Width:

3.270 inches

Mounting Stud Length:

0.500 inches

End Application:

Various shore atc; instrument landing system an/grc-2 (v)

Furnished Items And Quantity:

Nut 6; washer 8

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.160 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

+0.0/+50.0 watts single indicator 2nd range

Mounting Stud Diameter:

0.112 inches

Features Provided:

Rectifier circuit and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 screw and 2 threaded stud

Operating Voltage Rating In Volts:

26.0 dc

Material:

Plastic

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0