

View Online at <https://aerobasegroup.com/nsn/6625-00-050-6561>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

2600.0

Overall Length:

2.685 inches

Overall Height:

3.969 inches

Overall Width:

3.969 inches

Mounting Stud Length:

0.750 inches

Environmental Protection:

Shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

4.240 inches

Furnished Items And Quantity:

Nut 8; washer 16

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.560 inches

Meter Body Diameter Behind Mounting Flange:

3.781 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0 to 15.0 amperes, rf single indicator single range

Mounting Stud Diameter:

0.138 inches

Features Provided:

Internal shunting and transformer and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

1100 v peak working v to ground

Material:

Plastic phenolic

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Complies w/ansi c-39.1 spec

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0