NSN 6625-00-052-6076

Electrical Frequency Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-052-6076
Circuit Current For Which Designed:
Ac
Overall Length:
2.950 inches
Mounting Hole Diameter:
0.125 inches
Scale Division Quantity:
10 single indicator single range
Frequency Rating:
Between 55.0 hertz and 65.0 hertz
Overall Diameter:
2.696 inches
Environmental Protection:
Cold resistant and dust resistant and fungus resistant and humidity resistant and shock resistant and vibration resistant and water resistan
and windproof
Mounting Bolt Circle Diameter:
2.469 inches
Furnished Items And Quantity:
Nut 3; lockwasher 3
Indicator Type:
Vibrating reed
Installation Design:
Panel
Register Quantity:
2
Mounting Arrangement Style:
Three hole/stud bolt circle
Frequency Response Range:
+55.000 to 65.000 hertz
Dial Scale Marking Color:
Black single indicator single range
Resonant Reed Quantity:
11
Accuracy In Percent:
-0.3 to 0.3 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
2.579 inches
Meter Body Diameter Behind Mounting Flange:
2.096 inches
Movement Type:
Vibrating reed

White single indicator single range

Background Color:

NSN 6625-00-052-6076 Electrical Frequency Meter - Page 2 of 2



Power Source:
External
Mounting Facility Type And Quantity:
3 screw and 3 unthreaded hole
Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+55.0 to 65.0 hertz single indicator single range
Scale Selection Method:
Terminal
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder stud
Operating Voltage Rating In Volts:
Between 100.0 ac and 150.0 ac
Phase:
Single
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Cadmium
Special Test Features:
Complies with mil-m-10304
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A310a0