

View Online at <https://aerobasegroup.com/nsn/6625-00-052-6076>

Circuit Current For Which Designed:

Ac

Overall Length:

2.950 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

10 single indicator single range

Frequency Rating:

Between 55.0 hertz and 65.0 hertz

Overall Diameter:

2.696 inches

Environmental Protection:

Cold resistant and dust resistant and fungus resistant and humidity resistant and shock resistant and vibration resistant and water resistant and windproof

Mounting Bolt Circle Diameter:

2.469 inches

Furnished Items And Quantity:

Nut 3; lockwasher 3

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

2

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+55.000 to 65.000 hertz

Dial Scale Marking Color:

Black single indicator single range

Resonant Reed Quantity:

11

Accuracy In Percent:

-0.3 to 0.3 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.579 inches

Meter Body Diameter Behind Mounting Flange:

2.096 inches

Movement Type:

Vibrating reed

Background Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+55.0 to 65.0 hertz single indicator single range

Scale Selection Method:

Terminal

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder stud

Operating Voltage Rating In Volts:

Between 100.0 ac and 150.0 ac

Phase:

Single

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Cadmium

Special Test Features:

Complies with mil-m-10304

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0