

View Online at <https://aerobasegroup.com/nsn/6625-00-053-8255>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

2.650 inches

**Mounting Hole Diameter:**

0.125 inches

**Scale Division Quantity:**

30 single indicator single range

**Frequency Rating:**

400.0 hertz

**Overall Diameter:**

2.695 inches

**Environmental Protection:**

Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight

**Mounting Bolt Circle Diameter:**

2.440 inches

**Furnished Items And Quantity:**

Nut 7; lockwasher 5; seal 1

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Frequency Response Range:**

+360.000 to 440.000 hertz

**Dial Scale Marking Color:**

White single indicator single range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator single range

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

1.600 inches

**Meter Body Diameter Behind Mounting Flange:**

2.210 inches

**Movement Type:**

Moving iron vane

**Background Color:**

Black single indicator single range

**Pointer Color:**

White single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 screw and 3 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0 to 30.0 volts, ac single indicator single range

**Scale Selection Method:**

Terminal

**Features Provided:**

Luminous scale marking and magnetic shield and zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 solder lug

**Phase:**

Single

**Special Features:**

Ruggedized

**Material:**

Stainless steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel semigloss

**Special Test Features:**

Complies with mil-m-10304

**Surface Treatment Specification:**

Mil-f-14072 military specification single treatment response

**Style Designator:**

Round flush mtg

**Supplementary Features:**

4 volt-amperes maximum power consumption

**Test Data Document:**

81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-m-10304/6 government specification

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/A

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A310a0

**Mil-std (military Standard):**

Mil-f-14072 spec.