

View Online at <https://aerobasegroup.com/nsn/6625-00-054-2038>

Circuit Current For Which Designed:

Dc

Overall Length:

2.000 inches

Scale Division Quantity:

10 single indicator single range

Mounting Stud Length:

Between 0.375 inches and 0.625 inches

Overall Diameter:

2.695 inches

Mounting Bolt Circle Diameter:

2.440 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+55.000 to 65.000 hertz

Sensitivity Rating:

200.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.600 inches

Meter Body Diameter Behind Mounting Flange:

2.210 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

White single indicator single range

Mounting Facility Type And Quantity:

3 flange

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+55.0 to 65.0 hertz single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Magnetic shield

Criticality Code Justification:

Feat

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Operating Voltage Rating In Volts:

65.0 ac

Special Features:

Weapon system essential

Special Markings:

Red line at 60 hertz

Style Designator:

Round flush mtg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0