

View Online at <https://aerobasegroup.com/nsn/6625-00-054-3861>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

2.000 inches

Scale Division Quantity:

4 single indicator single range

Overall Diameter:

2.218 inches

Environmental Protection:

Dust resistant and fungus resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

5.0 amperes

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-0.5 to 0.5 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.781 inches

Meter Body Diameter Behind Mounting Flange:

2.000 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 bracket

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-5.0/+5.0 amperes, dc single indicator single range

Circuit Construction Type:

Nonelectronic

Scale Selection Method:

Terminal

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Sealed

Special Markings:

Discharge on bottom left side; charge on bottom on right side on scale

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Anodize

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0