

View Online at <https://aerobasegroup.com/nsn/6625-00-054-3861>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Overall Length:**

2.000 inches

**Scale Division Quantity:**

4 single indicator single range

**Overall Diameter:**

2.218 inches

**Environmental Protection:**

Dust resistant and fungus resistant and humidity resistant and shock resistant and vibration resistant and water resistant

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Sensitivity Rating:**

5.0 amperes

**Dial Scale Marking Color:**

White single indicator single range

**Accuracy In Percent:**

-0.5 to 0.5 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

0.781 inches

**Meter Body Diameter Behind Mounting Flange:**

2.000 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

Black single indicator single range

**Pointer Color:**

White single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

1 bracket

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

-5.0/+5.0 amperes, dc single indicator single range

**Circuit Construction Type:**

Nonelectronic

**Scale Selection Method:**

Terminal

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Sealed

**Special Markings:**

Discharge on bottom left side; charge on bottom on right side on scale

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Anodize

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A310a0