

View Online at <https://aerobasegroup.com/nsn/6625-00-054-7688>

Circuit Current For Which Designed:

Ac

Overall Length:

2.625 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 2.240 inches and 2.260 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 2.240 inches and 2.260 inches

Overall Height:

Between 2.984 inches and 3.130 inches

Overall Width:

Between 2.984 inches and 3.130 inches

Scale Division Quantity:

30 single indicator single range

Frequency Rating:

60.0 hertz

Mounting Stud Length:

0.500 inches

Environmental Protection:

Shock resistant and vibration resistant

Furnished Items And Quantity:

Nut 4; washer 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.010 inches

Meter Body Diameter Behind Mounting Flange:

Between 2.734 inches and 2.800 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 150.0 volts, ac single indicator single range

Mounting Stud Diameter:

0.112 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Meter iaw mil-m-6b

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0