

View Online at <https://aerobasegroup.com/nsn/6625-00-055-2706>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

2.000 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

12 single indicator single range

Overall Diameter:

3.468 inches

Environmental Protection:

Cold resistant and corrosion resistant and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

3.062 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

500.0 microamperes

Dial Scale Marking Color:

Black and blue and red single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.218 inches

Meter Body Diameter Behind Mounting Flange:

2.656 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 60.0 kilowatts single indicator single range

Scale Selection Method:

Terminal

Features Provided:

External shunting and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 screw and 2 solder lug

Special Features:

Shunt wire on back of meter

Special Markings:

Blue line at 38 kilowatts; red line at 45 kilowatts

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Anodize

Special Test Features:

Complies with mil-m-10304

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0