

View Online at <https://aerobasegroup.com/nsn/6625-00-056-1210>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

2.187 inches

Overall Height:

2.750 inches

Overall Width:

3.125 inches

Scale Division Quantity:

50 single indicator single range

Mounting Stud Length:

0.531 inches

Environmental Protection:

Cold resistant and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Mounting Bolt Circle Diameter:

2.440 inches

Furnished Items And Quantity:

Nut 5; lockwasher 5

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.968 inches

Meter Body Diameter Behind Mounting Flange:

2.156 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+10.0 amperes, dc single indicator single range

Circuit Construction Type:

Nonelectronic

Mounting Stud Diameter:

0.093 inches

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic and steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0