

View Online at <https://aerobasegroup.com/nsn/6625-00-058-2595>

Circuit Current For Which Designed:

Ac

Overall Length:

4.620 inches

Overall Height:

2.838 inches

Overall Width:

2.838 inches

Scale Division Quantity:

64 single indicator 3rd range

End Application:

Nimitz class cvn, kidd class ddg, arleigh burke class ddg, wasp class lhd, ticonderoga class cg (47), oliver perry class ffg, Forrestal class cv, Spruance class dd (963), Virginia class CGN (41)

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.693 inches

Meter Body Diameter Behind Mounting Flange:

2.750 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

2 slotted hole

Scale Graduation Type:

Nonlinear single indicator 1st range

Measurement Range:

-15.0 to 2.0 decibels single indicator 1st range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Criticality Code Justification:

Feat

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

3 solder lug

Special Features:

Weapon system essential

Material:

Plastic

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0