

View Online at <https://aerobasegroup.com/nsn/6625-00-058-8667>

Circuit Current For Which Designed:

Dc

Overall Length:

1.562 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.781 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.781 inches

Overall Height:

1.781 inches

Overall Width:

1.781 inches

Mounting Hole Diameter:

0.125 inches

Environmental Protection:

Airtight and dust tight

Furnished Items And Quantity:

Nut 4; lockwasher 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

200.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.000 inches

Meter Body Diameter Behind Mounting Flange:

1.500 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0 to 1000.0 watts single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Knife edge pointer

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder stud

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0