

View Online at <https://aerobasegroup.com/nsn/6625-00-059-4408>

Circuit Current For Which Designed:

Dc

Overall Length:

3.500 inches

Overall Height:

1.000 inches

Overall Width:

3.250 inches

Scale Division Quantity:

40 single indicator single range

Mounting Stud Length:

0.500 inches

Environmental Protection:

Dustproof

Distance Between Mounting Facility Centers:

2.938 inches

Barrel Width:

1.6875 inches

Furnished Items And Quantity:

Bracket 1; mtg hdw 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

78.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Panel For Which Designed:

Magnetic

Meter Depth Behind Mounting Flange:

3.000 inches

Meter Body Width Behind Mounting Flange:

2.500 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 bracket and 2 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+30.0/+70.0 microamperes, dc single indicator single range

Circuit Construction Type:

Nonelectronic

Mounting Stud Diameter:

0.125 inches

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

1.21875 inches

Meter Barrel Depth:

1.750 inches

Features Provided:

Electrical overload protection and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder stud

Special Features:

Ruggedized

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg barrel, down

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0