

View Online at <https://aerobasegroup.com/nsn/6625-00-060-0467>

Circuit Current For Which Designed:

Dc

Mounting Hole Diameter:

0.203 inches

Overall Diameter:

4.510 inches

Mounting Bolt Circle Diameter:

4.125 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

150.0 millivolts

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.660 inches

Meter Body Diameter Behind Mounting Flange:

3.550 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator single range

Power Source:

External

Measurement Range:

+0.0 to 50.0 microamperes, dc single indicator 1st range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Special Markings:

Red band from 40 to 50 ua on the 0 to 50 ua scale, red line at 30 ua on the 30 to 300 ua scale

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0