

View Online at <https://aerobasegroup.com/nsn/6625-00-060-3320>

Circuit Current For Which Designed:

Ac

Overall Length:

18.000 inches

Overall Height:

11.000 inches

Overall Width:

13.000 inches

Scale Division Quantity:

1 single indicator single range

Frequency Rating:

Between 40.0 hertz and 100.0 hertz

Furnished Items And Quantity:

1 coaxial free plug, type bnc

Indicator Type:

Dial w/pointer

Installation Design:

Bench

Frequency Response Range:

+4.000 to 1024.000 megahertz

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-3.0 to 3.0 at full scale single indicator single range

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+4.0 to 1024.0 megahertz single indicator single range

Scale Selection Method:

Switch

Features Provided:

Internal frequency calibrating crystal

Operating Voltage Rating In Volts:

Between 200.0 ac and 250.0 ac

Phase:

Single

Special Features:

Direct measurement of deviation from 200 hz to 125 khz, extended down to 10 hz using external readout; modulation frequency range: 50 hz to 35 khz; crystal locking allows measurement of fm noise; built-in deviation standard ensures high accuracy

Functional Description:

Direct reading fm deviation meter with calibrated carrier frequency range and 4 deviation ranges

Material:

Aluminum

Style Designator:

Rectangular or square

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0