

View Online at <https://aerobasegroup.com/nsn/6625-00-060-3320>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

18.000 inches

**Overall Height:**

11.000 inches

**Overall Width:**

13.000 inches

**Scale Division Quantity:**

1 single indicator single range

**Frequency Rating:**

Between 40.0 hertz and 100.0 hertz

**Furnished Items And Quantity:**

1 coaxial free plug, type bnc

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Bench

**Frequency Response Range:**

+4.000 to 1024.000 megahertz

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-3.0 to 3.0 at full scale single indicator single range

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+4.0 to 1024.0 megahertz single indicator single range

**Scale Selection Method:**

Switch

**Features Provided:**

Internal frequency calibrating crystal

**Operating Voltage Rating In Volts:**

Between 200.0 ac and 250.0 ac

**Phase:**

Single

**Special Features:**

Direct measurement of deviation from 200 hz to 125 khz, extended down to 10 hz using external readout; modulation frequency range: 50 hz to 35 khz; crystal locking allows measurement of fm noise; built-in deviation standard ensures high accuracy

**Functional Description:**

Direct reading fm deviation meter with calibrated carrier frequency range and 4 deviation ranges

**Material:**

Aluminum

**Style Designator:**

Rectangular or square

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A310a0